



RP65

MEETING STILE SEALS



A refrigeration type vinyl magnetic strip in an anodised aluminium channel which is morticed into the stiles of pivot, sliding or butt hinged double doors, to form an effective meeting stile seal (astragal). The magnetic strip is locked in place to prevent creeping and has sufficient strength that latches may not be required (centre latching cannot be used).

Can be used in conjunction with Raven door bottom and perimeter seals.

Note: RP65 is best suited to infrequent use and door closer hold open applications.

SPECIFICATIONS

Location

Meeting stiles of double swinging and sliding timber doors.

Size/Length

2250mm, 3000mm

Fixing

Adhesive Fixed, Push-in Friction Fit

Fixing Note

Push-in locking fit into a 16.5mm x 12mm deep groove and optional adhesive. Minimum door thickness of 40mm required.

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

Min & Max Gap

5mm to 7mm

Available Colours

Silver Anodised

Material

Aluminium

Material Description

Anodised aluminium with black PVC gasket and magnet strip.

Note: Architectural perimeter seal and door bottom extrusions are anodised 15µm and threshold plates are anodised 25µm for maximum durability. Black aluminium is anodised 25µm to 40µm.

Door/Frame Construction

Timber

Door Type

Double Inward Opening, Double Outward Opening, Sliding

Gap Description

(Swing doors)

User determined gap

No

Prior to installation gap

No

APPROVALS**Energy AUS/NZ**

ABC Housing Provisions Standard 2022 13.4.4, NCC J5D5

VARIATIONS**Product Code****Colour****Length**

A65C2250

Silver Anodised

2250mm

A65C3000

Silver Anodised

3000mm

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance