



## RP5

DOOR BOTTOM SWEEP SEALS



A Flexible EPDM weather strip sweep seal that fits to the bottom of doors. It is ideal for screen doors and sash windows to prevent insects from entering up the face of the glass. It is quick and easy to install to the door bottom, being fitted without removing the door. It is also ideal for garage tilt-up doors. Can be used in conjunction with Raven RP13 and RP82 threshold plates.

### SPECIFICATIONS

**Location**

Bottom of doors, sash windows or around stiles of tilt up doors.

**Size/Length**

920mm, 1000mm, 1250mm, 2250mm, 3000mm

**Fixing**

Screw Fixed

**Fixing Note**

Screw fix. Zinc plated, cross recess head S.T. screws supplied.

**Min & Max Gap**

0mm to 15mm

**Replacement Seals**

[RP303](#)

**Available Colours**

Bronze Anodised, Painted (Extra Cost), Silver Anodised

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

**Material**

Aluminium

**Door/Frame Construction**

Timber, Aluminium

**Door Type**

Single Inward Opening, Single  
Outward Opening, Double Inward  
Opening, Double Outward  
Opening, Security Screen, Bi-fold

**Material Description**

Anodised aluminium with solid  
EPDM gasket.

Note: Architectural perimeter seal  
and door bottom extrusions are  
anodised 15µm and threshold  
plates are anodised 25µm for  
maximum durability. Black  
aluminium is anodised 25µm to  
40µm.

**Garage Door Type**

Tilt-up

**Window Type**

Single Hung Sash, Double Hung  
Sash

**User determined gap**

Yes

**Prior to installation gap**

No

## APPROVALS

**Fire Flammability Index**

Gasket flammability index < 5 when tested to  
AS1530.2

**Energy AUS/NZ**

ABC Housing Provisions Standard 2022 13.4.4, NCC  
J5D5

**Insects & Vermin AUS/NZ**

AS 4674 Sect. 2.1.5 Pt. (iv), AS 4674 Sect. 2.1.7

## VARIATIONS

**Product Code**

**Colour**

**Length**

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

A5B1250	Bronze Anodised	1250mm
A5B3000	Bronze Anodised	3000mm
A5C1000	Silver Anodised	1000mm
A5C1250	Silver Anodised	1250mm
A5C2250	Silver Anodised	2250mm
A5C3000	Silver Anodised	3000mm
A5P1250	Painted (Extra Cost)	1250mm
A5P3000	Painted (Extra Cost)	3000mm
R5B	Bronze Anodised	920mm
R5C	Silver Anodised	920mm

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

# FITTING INSTRUCTIONS

## RP5 - Weather Strip Door Seal



### HOW TO FIT RP5

**Note:** Note: For inward opening doors check that floor level is even otherwise seal may jam. Flexible seal should lightly engage the sealing surface and sweep smoothly across the floor. Uneven or ramped floors may cause the seal to drag. Recommended adhesion temperature is above 21°C. Allow a few days for full adhesion strength to occur.

- Seal can be fitted to the inside or outside of the door. Surface must be clean, smooth and if painted, well cured. *Note: Self-adhesive seals will not stick to oil-rub finishes.*

**FIG.A** (section view)

