



## RP56

DOOR FRAME / PERIMETER SEALS



A PVC finned sweep seal designed to fit into a groove around the perimeter of a timber door or frame to reduce noise and air movement. This unobtrusive seal is discrete in appearance and does not restrict the doors operation.

The RP56 can be used in conjunction with Raven automatic door bottom seals and brush strip seals.

Note: Check latching requirements.

### SPECIFICATIONS

<p><b>Location</b> Perimeter of internal timber doors or frame.</p>	<p><b>Size/Length</b> 1000mm, 2250mm, 3000mm</p>	<p><b>Fixing</b> Adhesive Fixed</p> <p><b>Fixing Note</b> Adhesive fix (by installer) into a 10mm x 4mm groove.</p>
<p><b>Min &amp; Max Gap</b> 2mm to 4mm</p>	<p><b>Replacement Seals</b> <a href="#">RP469</a></p>	<p><b>Available Colours</b> Bronze Colour</p>
<p><b>Material</b> Rigid PVC</p> <p><b>Material Description</b> Rigid PVC holder with flexible PVC gasket.</p>	<p><b>Door/Frame Construction</b> Timber</p>	<p><b>Door Type</b> Single Inward Opening, Single Outward Opening, Double Inward Opening, Double Outward Opening, Sliding, Pivot</p>

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

**User determined gap**

No

**Prior to installation gap**

No

## APPROVALS

**Fire AUS/NZ**

AS 1530.4, AS 1905.1, NCC S12C2, NZBC C/AS2  
4.16.2(a) & App C6.1.1

**Fire UK/EU**

Approved Document B, Tests above are similar to BS  
EN 1634-1 & BS 476 Pt. 20 & 22

**Fire Rating**

Up to FRL & FRR-/90/30, Up to FD60 (on door bottom  
only)

**Energy AUS/NZ**

NCC J5D5, ABCB Housing Provisions Standard 2022  
13.4.4

## VARIATIONS

**Product Code****Colour****Length**

A561000

Bronze Colour

1000mm

A562250

Bronze Colour

2250mm

A563000

Bronze Colour

3000mm

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance