



## RP73

MEETING STILE SEALS



An extremely Flexible co-extruded PVC sweep seal that fits into a saw kerf groove cut into the frame or door. It holds tight radii and compound curves when bent around a frame. It resists UV, ozone, mildew and colour change.

The RP73 can be used in conjunction with Raven automatic door bottom seals and brush strip seals.

### SPECIFICATIONS

**Location**

Perimeter of timber sliding doors, pivot doors and door frames.

**Size/Length**

1000mm (sold in coils of 1m increments), 200m coil (2 x 100m)

**Fixing**

Push-in Friction Fit

**Fixing Note**

Push-in locking fit into a 2.5mm x 6mm deep kerf groove.

**Min & Max Gap**

6mm to 8mm

**Available Colours**

Brown

**Material**

Rigid and Flexible PVC

**Door/Frame Construction**

Timber

**Door Type**

Single Inward Opening, Single Outward Opening, Double Inward Opening, Double Outward Opening, Sliding, Pivot

**User determined gap**

No

**Prior to installation gap**

No

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

**APPROVALS**

Energy AUS/NZ

ABC Housing Provisions Standard 2022 13.4.4, NCC J5D5

**VARIATIONS**

Product Code	Colour	Length
OEM73	Brown	200m coil (2 x 100m)
A73	Brown	1000mm (sold in coils of 1m increments)

**Product Sizes/Lengths:** Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance