



RP510

MEETING STILE SEALS



A compression seal, made from silicon. Raven silicon has a high resistance to permanent set (memory). It will not absorb water and is resistant to ozone and ultra-violet light deterioration.

SPECIFICATIONS

Location

Aluminium, PVC or timber door and window frame grooves where dimensions suit.

Size/Length

24m coil, 100m coil

Fixing

Push-in Friction Fit

Push-in locking fit into a 3.5mm x 5mm deep kerf groove.

Min & Max Gap

3mm to 5mm

Available Colours

Black, Brown, White

Material

Silicon Rubber

Compression: 1mm to 2mm

Door/Frame Construction

Timber, Aluminium, PVC

Door Type

Single Inward Opening, Single Outward Opening, Double Inward Opening, Double Outward Opening, Sliding, Pivot, Security Screen, Bi-fold

Window Type

Awning (Outward Opening), Casement (Side Hung), Hopper (Inward Opening)

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

APPROVALS

Acoustic AUS/NZ

NCC F7D6

Weather AUS/NZAS/NZS 1170, NCC various sections, AS 2047, AS 4055,
AS 4420 Pt. 0 to 5**Energy AUS/NZ**ABC Housing Provisions Standard 2022 13.4.4, NCC
J5D5**Acoustic UK/EU**

Approved Document E, Rated to BS EN ISO 717-1

Weather UK/EUApproved Document L1 & L2, Tests above are similar
to BS 5368 & BS 7386

VARIATIONS

Product Code	Colour	Length
B510BK	Black	100m coil
B510BK24	Black	24m coil
B510B	Brown	100m coil
B510B24	Brown	24m coil
B510W	White	100m coil
B510W24	White	24m coil

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance