



RP28

THRESHOLD PLATES / RAMPS



RP28 is a wide, heavy duty threshold plate with a ribbed profile and integral sill gaskets. They are ideal for use with pivot hinge doors.

Can be used in conjunction with Raven door bottom seals to prevent rain, draughts, noise and smoke infiltration.

SPECIFICATIONS

Location

Door sill.

Size/Length

1000mm, 2000mm, 3000mm

Fixing

Screw Fixed

Fixing Note

Screw fix. Colour matched zinc plated, cross recess head CSK S.T. screws supplied.

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

Replacement Seals[RP404a](#)**Available Colours**

Silver Anodised

Material

Aluminium

Material Description

Anodised aluminium with flexible PVC gaskets.

Note: Architectural perimeter seal and door bottom extrusions are anodised 15µm and threshold plates are anodised 25µm for maximum durability. Black aluminium is anodised 25µm to 40µm.

User determined gap

No

Prior to installation gap

No

APPROVALS**Access & Mobility AUS/NZ**

NZBC D1/AS1 1.3.2

Access & Mobility UK/EU

Approved Document M

Accreditations

ANSI/BHMA: A156.21

Fire AUS/NZAS 1530.4, AS 1905.1, NCC S12C2, NZBC C/AS2
4.16.2(a) & App C6.1.1**Fire UK/EU**BS 476 Pt. 20 & 22 (similar to BS EN 1634-1), Approved
Document B**Fire Rating**

Up to FD120, Up to FRL & FRR-/240/30

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance

BAL Statement

BAL FZ when used with a BAL rated door bottom seal
in accordance with AS3959

VARIATIONS

Product Code	Colour	Length
A28C1000	Silver Anodised	1000mm
A28C2000	Silver Anodised	2000mm
A28C3000	Silver Anodised	3000mm

Product Sizes/Lengths: Product lengths greater than 2m can only be purchased from Raven distributors and stockists. Please contact Raven Sales for assistance