



AMERICA'S NO.1 FAUCET BRAND

Arbor spot resist stainless one-handle high arc pulldown kitchen faucet

Features

Arbor's smooth profile is tailored to perfection. The slight flair of the handle and the curve of the spout make this a transitional look that works with a variety of decorating styles.

- Spot Resist™ stainless finish resists fingerprints and water spots for a cleaner looking kitchen
- Equipped with the Reflex™ system for smooth operation, easy movement and secure docking of the pulldown/pullout spray head
- Features Duralock™ quick connect system for easy installation
- Pulldown design offers at-your-fingertips water delivery
- One-handle lever handles make it easy to adjust the water
- Aerated stream for everyday cleaning; pause function lets you conveniently stop water flow from the spray head; powerful rinse for heavy-duty cleaning
- Single hole mount creates a cleaner look against custom countertops
- Complies with Americans with Disabilities Act (ADA) specifications
- Meets current legislation, including ab1953 (california) and s152 (vermont)





AMERICA'S NO.1 FAUCET BRAND

Specifications

FAUCET DESCRIPTION

- Reflex™ pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Hydrolock® quick connect installation
- Pullout spray with 68" braided hose
- Flexible supply lines with 3/8" compression fittings
- High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout

OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pullout or retracted position
- When filling a vessel outside the sink, the pause feature conveniently stops the flow of water as the wand passes over the counter top

FLOW

- Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow


- ADA



ARBOR™ Single Handle High Arc Pulldown Kitchen Faucet

Models: 7594SRS

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 OR 3 HOLES, 1-1/2" (38mm) MIN. DIA.



CRITICAL DIMENSIONS

(DO NOT SCALE)