



Technical Data Sheet

BaseCoat - No More Stains B105 - Oil Based

DESCRIPTION

Selleys BaseCoat No More Stains B105 is a oil based paint ideal for locking in waterbased stains on all interior and exterior surfaces. It is suitable in all situations as primer, sealer and undercoat.

SIZES AVAILABLE

Available in 1L & 5L, and is white in colour.

USES

Selleys BaseCoat No More Stains B105 is an interior and exterior stain sealer. Ideal in covering waterbased stains, food and beverage stains and graffiti.

TECHNICAL FEATURES

- **Ideal for water stains** - Cover water based stains bleeding through subsequent coats of paint
- **Superior tannin blocking** - Stop tannin bleeding through subsequent coats of paint, thereby preventing topcoat discolouration
- **For interior and exterior use** - Versatile

HOW TO USE

Surface Preparation

Stained surfaces

Remove as much of the stain as possible by washing, sanding, scraping, etc.

Previously painted surfaces

Ensure surface is clean and free from dust, dirt, grease and oil. Remove any loose, peeling, flaking or chalky paint by sanding or scraping. Before applying No More Stains B105 rinse surface to be painted with clean water and allow the surface to completely dry.

Bare timber

Sand bare timber to a clean surface. Fill nail holes and cracks with a suitable filler then sand smooth and dust off

Cement render and plaster

Clean surface to remove all loose and flaking materials and contaminants.

Application

By brush or roller. Before applying- stir product with a broad, flat paddle. Apply one even coat of Selleys No More Stains B105. Heavily stained surfaces may require a second coat of Selleys No More Stains B105.

Thinning

Not usually required. In hot conditions or on porous surfaces use up to 100ml of mineral turpentine per litre.

CLEAN UP

Clean all tools with Mineral Turpentine.

TECHNICAL DETAILS

Typical Properties

Gloss Level:	Flat
Solid Content:	40.0%
Number of coats:	1
Wet film per coat:	recommended 100µm
Dry film per coat:	recommended 40µm
Recoat:	1 Hour
Thinner:	Mineral Turpentine
Coverage:	12.0sqm/L
Toxicity:	Lead free. Dry film is non-toxic
Touch Dry:	30 minutes
Heat Resistance:	Up to 120 °C intermittently

LIMITATIONS

- Do not apply if the surface temperature is below 10 °C or conditions indicate it will fall below 10 °C during the drying period.

WARNINGS/FIRST AID

This material is classified as hazardous according to the ASCC. Keep out of reach of children. Irritating to eyes & skin.

If swallowed: Do not induce vomiting. Drink plenty of water and contact a doctor. Eye contact: Hold eye open, and flood with water for at least 15 minutes and see a doctor.

Skin contact: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. Provide adequate ventilation during use. If painting indoors, keep windows and doors open during use and while drying. Highly Flammable Vapour can be ignited by flame or spark. Refer to Material Safety Data Sheet for more information.

SHIPPING/STORAGE/DANGEROUS GOODS INFORMATION

Storage

Store in cool dry place away from sources of heat & ignition and as required by regulations for storage of low flash point flammable liquids.

Transport - Class 3, UN1263, PGIII.