

キヤスオ CASTLE

PREMIUM
WATERPROOFING

PME-899 (Concrete Sealer)

CASTLE PME-899 clogs micro pores of concrete surfaces. Has strong cementing power to concrete with high-solid content. It saves your time. PME-899 is non-toxic and non-flammable. Can be use to all concrete surfaces.



Function

- Designed to solve problems of porosity on all concrete/stone.
- Excellent base coat clogs all micro pores.
- Excellent adhesion to Acrylic Paint (topcoat).
- Bonds with concrete surface, penetrates up to 4mm-5mm depth with water repellent properties.
- As Mortar Intensifier, guaranteed to stop water even under pressure, for interior, exterior, above and below grade concrete surfaces.

Application Procedure

- Clean and dry surface completely before applying.
- Can be applied using either brush or roller.
- Apply 1 to 2 coats or more of PME-899 (application depends on the porosity of the concrete)
- Let it dry for 1hr. (direct sunlight) before applying Skim Coat/ Latex Paint.

Area Coverage:

- 4 kgs/4 liters = 24 m²(267 f²)
to 26 m²(289 f²)
- 10kgs/10 liters = 60 m²(667 f²)
to 65 m²(722 f²)

Standard Formula:

- PME-899 = 4 liters or 4 kgs / 12.5 %
- WATER = 1.6 liters or 1.6 kgs / 5 %
- CEMENT = 6.8 kgs / 21.25 %
- SAND = 19.6 kgs / 61.25 %