



# Door Frame or Perimeter Seals

RP120



Delta Seal™

RP120 is a co-extruded PVC, acoustic and smoke seal. Discreetly located in the protected corners of rebated timber or steel door frames. RP120 is suitable for new and retrofit applications.

## Location

Around rebated frames of single or double broad butt hinged doors and windows.

**Min/MaxGap** 3mm - 5.5mm.

**Seal Sizes Available** in door set sizes.

**Standard Finish** Black (PVC).

## Fixing Method

Self adhesive.

**Note:** Contact surface must be clean, smooth and if painted, well cured.

## Seal Material

Rigid and Flexible flame

retardant PVC, with an aggressive self adhesive backing tape on both sides of the rigid carrier.

## Used in conjunction

Raven door bottom seals, astragal and threshold plates.

## Approvals

### Acoustic

UK/EU: Conforms to Approved Document E. Tested to BS EN ISO 140.3, similar to BS EN ISO 717.1, BS 2750, BS 5821.

AUS/NZ: Conforms to BSA Sect. F5.5 Tested to AS 1191 (similar to AS 1045, AS/NZS 1276).

### Fire & Smoke

AUZ/NZ: Conforms to BCA Spec. C3.4, Tested to AS 1530.4 & AS/NZS 1905.1

UK/EU: Conforms to Approved Document B. (Tests above are similar to BS EN 1634.1, BS 476 Part 20 & 22)

