



# Door Frame or Perimeter Seals

RP24

H



An adjustable door stop seal for noise, light and smoke. The RP24 seal uses independently adjustable fasteners to achieve up to 8mm sealing adjustment for maximum noise control.

The seal can be butt jointed at the corners of the frame to produce an easily installed continuous seal around the door frame, replacing the conventional doorstop on either steel or timber door frames. It is tamper proof with fully concealed fasteners to give the seal an aesthetic appearance. The closed cell S.E. Sponge E.P.D.M. seal requires only normal door closing force. If fixing to rebated frames of single doors, specify a long backset door latch. RP24 has been granted an Australian Design Award.

**Location** Head and jamb of single or double broad butt hinged doors.

**Min/Max Gap** 0mm/8mm.

**Seal Sizes** Available in stock lengths or door set sizes.

**Standard Finish** Aluminium anodised 15 microns. Satin Clear (Silver) or Bronze finish.

P.E. Paint (extra cost). Is a two pack polyester enamel colour match finish which is equal to or exceeds powdercoat finish.

**Fixing Method** Zinc plated, cross recess head S.T. screws of the appropriate size are supplied.

**Adjustment** Can be adjusted by 8mm Independently of the fixing screws.

**Seal Material** Closed cell EPDM sponge, self extinguising (black).

**Replacement Seal** RP338 (silicon option RP338Si).  
**Note:** different profile.

**Approvals**  
**Acoustic AUS/NZ:** Conforms to BCA Sec. F5.5. Tested to AS 1191, AS 1045, AS/NZS 1276.  
**UK/EU:** Conforms to Approved Document E. Tested to BS EN ISO140.3 (similar to BS EN ISO 717.1, BS2750 BS 5821).

