



Door Frame or Perimeter Seals

RP93 Si



A weather and acoustic seal suitable for plain or rebated frames. RP93Si is quick and easy to install (mitre joint only), to the head and jambs without removing the door. Slotted for installation adjustment, the soft silicon bulb accommodates a tighter seal and, with a tamper proof cover strip, provides a fit and forget feature.

Note: If fixing to rebated frames of single doors specify a long backset door latch. The tamper proof aluminium coverstrip is not recommended for removal once installed, refer RP78Si or RP10Si for this feature.

Location

Head and jambs of single or double broad butt hinged doors.

Min/MaxGap

0mm - 6mm.

Seal Sizes Available in stock lengths or door set sizes. Maximum length 3000mm.

Standard Finish Cover strip only. Aluminium anodised 15 microns. Satin clear (Silver) or Bronze finish.

P.E. Paint (extra cost). Is a two pack polyester enamel colour match finish which is equal to or exceeds powdercoat finish.

Fixing Method Zinc plated, cross recess head S.T.screws of the appropriate size are supplied.

Seal Material

Silicon Rubber (SE) (charcoal).

Replacement Seal RP393 Si.

Used in conjunction

RP8 Si, RP16 Si, Rp38 Si, RP99 Si, RP70 Si, RP97 Si.

Approvals

Fire & Smoke AUZ/NZ: Conforms to BCA Spec. C3.4, Tested to AS 1530.4 & AS/NZS 1905.1

UK/EU: Conforms to Approved Document B. (Tests above are similar to **BS EN 1634.1, BS 476 Part 20 & 22, Sec.31.1**)

Acoustic AUS/NZ: Conforms to BCA Sec. F5.5 Tested to AS1191. AS 1045, AS/NZS 1276.

UK/EU: Conforms to Approved Document E. Tested to BS En ISO140.3 (similar to BS EN ISO 717.1, BS 2750, BS 5821).

