



# Door Frame or Perimeter Seals

RP94 Si



A weather and acoustic seal, suitable for rebated frames. RP94 Si is quick and easy to install, either mitred or butt jointed to the head and jambs without removing the door. Slotted for installation adjustment, the soft silicon bulb accommodates a tighter seal and with a tamper proof cover strip, provides a fit and forget feature.

**Note:** The tamper proof aluminium coverstrip is not recommended for removal once installed, refer RP78 Si for this feature.

## Location

Head and jambs of single or double broad butt hinged doors.

**Min/MaxGap** 0mm - 6mm.

**Seal Sizes** Available in stock lengths or door set sizes.

**Standard Finish** Cover strip only. Aluminium anodised 15 microns. Satin clear (Silver) or Bronze finish.

P.E. Paint (extra cost). Is a two pack polyester enamel colour match finish which is equal to or exceeds powdercoat finish.

**Fixing Method** Zinc plated, cross recess head S.T.screws of the appropriate size are supplied.

## Seal Material

Silicon Rubber (SE) (charcoal).

**Replacement Seal** RP394 Si.

## Used in conjunction

Raven door bottom seals, astragal and threshold plates.

## Approvals

**Fire & Smoke AUZ/NZ:** Conforms to BCA Spec. C3.4, Tested to AS 1530.4 & AS/NZS 1905.1

UK/EU: Conforms to Approved Document B. (Tests above are similar to **BS EN 1634.1, BS 476 Part 20 & 22**)

**Acoustic AUS/NZ:** Conforms to BCA Sec. F5.5 Tested to AS 1191. AS 1045, AS/NZS 1276.

UK/EU: Conforms to Approved Document E. Tested to BS EN ISO140.3 (similar to BS EN ISO 717.1, BS 2750, BS 5821).

